

www.kortherm.com

Since **1999**

# μ-LAB/FAB Series



## KORTherm Science Co.,Ltd.

We have wide range of selection for laser with 1064/532/355 wavelength and we can provide the complete sample test work corresponding to required applications.

C-1203B, Woolim Lions Valley, 283, Bupyeong-daero, Bupyeong-gu, Incheon, South Korea.

phone: +82-32-623-6320~4 | fax: +82-32-623-6325 | e-mail: kos@kortherm.co.kr



### Trusted Brand

Since 1999, we have served many customers like Samsung, LG, SNU, ETRI, KRICT, KIMS, KIST and so no.



### Customized Laser System

According to our customer requirement, we develop suitable and excellent product and provide nice after service.



### HOLOEYE Exclusive Agent


We provide the products of HOLOEYE Photonics AG, Germany like Spatial light modulator (SLM) and so no.





KORTherm Science Co.,Ltd.

TEL: 032-623-6320~4 E-Mail: kos@kortherm.co.kr

### Laser types

Sortation	Femto seconds	Pico seconds	Nano seconds	Fiber Laser
Photo				
Power	20 ~ 80W	~ 60W	~ 20W	20 ~ 200W
Wavelengths	1064 / 532 / 355nm	1064 / 532 / 355nm	532 / 355nm	355 ~ 1064nm




### Operation Mode

Operation mode	Dual Mode			IFOV	R2R
	Scan Mode	Direct Writing(Fixed Optics)			MOTF
		Objection Lens+ Motion Stage	Scanner + Motion Stage		
Model	μ-Lab, μ-Fab	μ-Fab		μ-Fab-I, μ-Gan	μ-R2R
Reference Photo					
Laser	355nm, 532nm	355nm, 532nm, 1064nm		355nm, 532nm, 1064nm(1 selection)	355nm, 532nm, 1064nm(1 selection)
Special Feature	Laser beam movement(using inside mirror) / Fixing the sample(Stage)	Fixing Laser beam Sample(Stage) movement		Laser beam movement+ Laser movement Fixing the sample(Stage)	Laser beam movement One axis(X axis) movement of sample(Stage)
Travel range	≤180mm x 180mm <sup>2</sup>	≤300 x 500mm <sup>2</sup>		≤500 x 500mm <sup>2</sup> ~ 1000 x 1000mm <sup>2</sup>	Web width (200~300mm)
Processing Velocity	≤5 ~ 7m/s	≤1 ~ 1.5m/s		≤1 ~ 1.5m/s	3M / min
Curve	0	△		0	△
Straight line	0	0		0	0
Video	www.kortherm.com				
Applications	Glass / Polymer / Wafer / Thin metal / Film / Silicon wafer DISPLAY (FPD, AMLCD) / Solar Cell (Perovskite, OPV, CIGS등) / Bio sensor				
Option	- Beam Profile(Tophap, Bessel Beam) - IFOV				

### CONTENTS

- Laser/Beam profile type .....2
- μ-Lab-S1 .....5
- μ-Lab-S2 .....9
- μ-Fab .....12
- μ-Fab-D2 .....17
- μ-WTU .....21
- μ-Gan .....24
- μ-Fab-I .....27
- μ-R2R .....30
- μ-Slot Die .....33
- μ-Lab CO2 .....35
- KOS software .....38
- Sample test service .....43
- SLM .....47

## Beam delivery technology

<p>Gaussian</p>	<ul style="list-style-type: none"> <li>• Typical shape of Laser Beam</li> <li>• Energy is concentrated in center</li> </ul>	 <p>Gaussian Beam Shape and Energy distribution</p>
<p>TOP HAT (Flat top Laser Beam)</p>	<ul style="list-style-type: none"> <li>• TModulated Beam of Gaussian</li> <li>• It have constant energy density</li> <li>• It make uniform Laser Processing result</li> <li>• Power is lower than Gaussian</li> </ul>	 <p>Top-Hat Beam Shape and Energy distribution</p>
<p>Bessel</p>	<ul style="list-style-type: none"> <li>• Beam have long focus position</li> <li>• It use process of Transparent material like glass, sapphire, quartz.</li> </ul>	 <p>Bessel Beam Diameter 2 ~ 3<math>\mu</math>m by Axicon Lens</p> <p>Energy distribution of Bessel Beam</p>

## LASER PATTERNING SYSTEM

# $\mu$ -Lab-S1

It is able to get the excellent performance of the cutting edges with minimum burr and debris particles applying the one of 3wavelengths (355nm, 532nm, 1064nm)a laser beam within 180 × 180mm<sup>2</sup> area by Scan Mode



# μ-Lab-S1

# μ-Lab-S1




## μ-Lab-S1

- Laser source : 1 selection of 1064 / 532 / 355nm
- Precisely small beam control
- Compact size design & simple operation
- Easy to use with combined one software
- 20/50/100W average output power


## Applications

- FTO / ITO patterning
- Lithium – ion cells cutting
- Si wafer dicing / scribing
- PCB micro hole drilling
- Scribing(thin metal ,ceramic)
- Edge isolation(Solar cell)
- Selective removal(multi-layered film)
- Compound ferrite cutting
- CFRP(carbon fiber reinforced plastic)cutting
- Etc.(polymer, sapphire, glass, quartz..)



## Software

The Laser Control Panel software for μ-LAB is developed for Windows. This multi-functional software allows operating the laser parameters and controlling all of the system precisely at a time.



## Dedicated vision software

μ-LAB Advanced has the dedicated software of the on-axis machine vision system. This multi-functional software allows not only image detection also quality control through live imaging marking.

### Application examples fiducial teaching

Reference mark (fiducial) selection

Fiducial teaching with 100 features

Fiducial teaching with 500 features

Reference mark teaching parameter:

- center recognition & orientation
- feature counts
- threshold for features
- removal of incorrect information
- blob recognition to get center by end points

### Application examples contour detection

Edge detection on SMD chip

Edge detection on solar cell

Contour detection of plastic key knob for day and night design

Contour teaching and detection



- Edge finder
- Inclined edges finder with search direction
- Blob finder
- Shape finder 1 + 2
- Grey value transition analysis

Inclines edges with search direction

— Camera optical path  
— Laser beam path

## Dedicated vision software (Self-Development)


μ-LAB Advanced has the dedicated software of the on-axis machine vision system. This multi-functional software allows not only image detection also quality control through live imaging marking.



## μ-Lab1 System - Single Wavelength

Laser / Wavelength	Pulsed (Nanosecond / Picosecond / Femtosecond)Single (1064nm / 532nm / 355nm)
Operation Mode	Galvano Scanner
Travel Range	180 x 180mm <sup>2</sup>
Accuracy	±0.5μm
Repeatability	±0.5μm
Vision Alignment	Off Axis Machine Vision System (2 Camera) Drawing pattern detection. Quality control, Pattern offset alignment.
Option	Autofocusing (by Substrate Thickness Reflection) Bessel Beam, Top Hat (Flat-top) Beam Porous Ceramic Substrate Chuck (Vacuum Fix)
Supported Drawing Format	DWG, DXF, JPEG
Application	FTO/ITO patterning / Lithium- ion cells cutting Si wafer dicing/scribing / PCB micro hole drilling Scribing(thin metal ,ceramic) / Edge isolation(Solar cell) Selective removal(multi-layered film) Compound ferrite cutting / CFRP(carbon fiber reinforced plastic)cutting / Etc.(polymer, sapphire, glass, quartz..) / Bio Sensor
Dimension (W x D x H). Weight	1250 x 950 x 1950(mm) , 0.8t

※ Alternative laser module for different wavelength , output power can be adapted depending on the applications



## LASER PATTERNING SYSTEM


# μ-Lab-S2

It is able to get the excellent performance of the cutting edges with minimum burr and debris particles applying the two of 3wavelengths (355nm, 532nm, 1064nm) laser beam within 180 × 180mm<sup>2</sup> area by Scan Mode



# μ-Lab-S2

# μ-Lab-S2



## μ-LAB-S2 (2 scanners)

- Laser source : 355 / 532 / 1064nm (2 Selective)
- Precisely small beam control
- Compact size design & simple operation
- Easy to use with combined one software
- 10 / 20 / 45W average output power


## μ-Lab-S2/S3 System - Multiple Wavelength

Laser / Wavelength	Pulsed (Nanosecond / Picosecond / Femtosecond), Dual / Triple (1064nm / 532nm / 355nm)
Operation Mode	Galvano Scanner
Travel Range	180 x 180mm <sup>2</sup>
Accuracy	±0.5μm
Repeatability	±0.5μm
Vision Alignment	Off Axis Machine Vision System (2 Camera) Drawing pattern detection. Quality control, Pattern offset alignment.
Option	Autofocusing (by Substrate Thickness Reflection) Bessel Beam, Top Hat (Flat-top) Beam, Porous Ceramic Substrate Chuck (Vacuum Fix)
Supported Drawing Format	DWG, DXF, JPEG
Application	FTO / ITO patterning / Lithium-ion cells cutting Si wafer dicing / scribing / PCB micro hole drilling Scribing(thin metal ,ceramic) / Edge isolation(Solar cell) Selective removal(multi-layered film) Compound ferrite cutting / CFRP(carbon fiber reinforced plastic)cutting / Etc.(polymer, sapphire, glass, quartz.) / Bio Sensor
Dimension (W x D x H). Weight	1700 x 1000 x 2050(mm) , 0.9t

※ Alternative laser module for different wavelength , output power can be adapted depending on the applications



## Applications

- FTO / ITO patterning
- Lithium – ion cells cutting
- Si wafer dicing / scribing
- PCB micro hole drilling
- Scribing(thin metal, ceramic)
- Edge isolation(Solar cell)
- Selective removal(multi-layered film)
- Compound ferrite cutting
- CFRP(carbon fiber reinforced plastic)cutting
- Etc.(polymer, sapphire, glass, quartz..)



## Software

The Laser Control Panel software for μ-LAB is developed for Windows. This multi-functional software allows operating the laser parameters and controlling all of the system precisely at a time.



LASER PATTERNING SYSTEM

**μ-FAB™**


This system makes it easy to select the beam shape (Gaussian, Top hap, Bessel mode) and working area (500 mm × 300 mm on fixed optic mode) according to user's purpose.



**μ-FAB™**


**Mo Patterning on Glass**

Molybdenum Layer thickness: 1μm  
 Substrate : glass (50mm x 50mm)  
 Processing speed : 1m/s  
 Patterning width : 10μm  
 No damage on glass  
 Isolation : >30MΩ




**ITO Patterning on CIGS Layer (GLASS + Mo + CIGS + ITO or ZnO)**

Layer thickness  
 · molybdenum : 0.4μm  
 · CIS/CIGS : 0.5μm  
 · ITO or ZnO : 0.5μm  
 Substrate : glass (50mm x 50mm)  
 Process speed : 2m/s  
 Patterning width : 10μm  
 Patterning depth : 3.5μm  
 No damage on CIS / CIGS multilayer  
 No damage on glass  
 Isolation : >30MΩ



**ITO patterning on glass (Si based solar panel)**

Layer thickness  
 · ITO : 1μm  
 · Glass : 0.7mm  
 Substrate : glass (200mm x 200mm)  
 Process speed : 1m/s  
 Patterning width : 20μm  
 Patterning depth : 1μm  
 No damage on Glass




# μ-FAB™

# μ-FAB™


## FTO Patterning on Glass

FTO Layer thickness : ~ 700nm  
 Substrate : glass (50mm x 50mm)  
 Processing speed : ~ 200μm/s  
 Patterning width : 10μm  
 No damage on glass  
 Isolation : >30MΩ




## ITO Patterning on Quartz (Quartz +ITO)

ITO Layer thickness ~ 150nm  
 Substrate : Quartz (50mm x 50mm)  
 Process speed : ~ 200nm/s  
 Patterning width : 10μm  
 No damage on quartz  
 Isolation : >30MΩ



## ITO patterning on glass

Layer thickness  
 · ITO : ~ 150nm  
 Substrate : glass or Quartz (200mm x 200mm)  
 Process speed : ~ 200nm/s  
 Patterning width : 20μm  
 No damage on glass  
 Isolation : >30MΩ





## μ-FAB™ TECHNICAL DATA

WORKSTATION	PICOSECOND LASER	OPTICAL SYSTEM
Granite base for vibration isolation Fume extraction system Clean room class: machine class 1000 Enclosure isolated from machine core Interlock work area door	Pico-second laser Mode locked pulsed fiber laser Wavelength : 1064 / 532 / 355nm Average power : <40W Laser mode : Single mode	Fixed Focusing Head Beam collimation mirror Turning mirror Spot size : approx. 10μm  Galvano scan head type Scanning area: 180mm x 180mm or more f-theta lens Beam spot size : <35μm
MOTION SYSTEM	VISION SYSTEM	DISPLACEMENT SENSOR
Travel range : 400mm x 400mm or more Motion speed : 700mm/s or more Resolution : 0.5μm Accuracy : ±1μm over full travel Repeatability : ±1μm over full travel Z-axis travel range : 20mm Z-axis resolution : 1μm	CCD resolution : >1Mpixel FOV (Field of view) : 600μm x 400μm Frame rate : 30fm Data output : IEEE 1394 Focusing lens Light : White type LED spot	Wavelength : 670nm Spot size : 2μm Resolution : 0.01μm Measurement Function : - 2D / 3D Profiler - Surface roughness(Ra, Rt, Rz)
SUBSTRATE MOUNT	SYSTEM CONTROLLER	S/W and etc
Vacuum chuck for glass and wafer Glass size : 200mm x 200mm or more Wafer : 4inch or more	Industrial PC Windows 10 based user interface Position synchronized laser firing Integrated operation of laser and stages	Auto-Alignment S / W Image recognition S / W Auto-Focus S / W High resolution microscope unit B / W CCD camera Control software

### P3 patterning on Glass


Mo thickness : 0.4μm  
 thickness : 3μm  
 Substrate : glass (50mm x 50mm)  
 Process speed : ~ 300nm/s  
 Patterning width : 10μm  
 Isolation : >30MΩ



## μ-Fab System

Laser / Wavelength	Pulsed (Nanosecond / Picosecond / Femtosecond) Single, Dual, Triple (1064nm / 532nm / 355nm)
Operation Mode	Direct Writing (Fixed Optic)
Travel Range	500mm <sup>2</sup> x 300mm <sup>2</sup> / 300mm <sup>2</sup> x 300mm <sup>2</sup> Linear motion stage application, depends on the requirement size
Accuracy	±0.5μm
Repeatability	±0.5μm
Vision Alignment	Off Axis Machine Vision System (1 Camera) Drawing pattern detection. Quality control, Pattern offset alignment.
Option	Bessel Beam, Top Hat (Flat-top) Beam
Supported Drawing Format	DWG, DXF, JPEG
Application	FTO / ITO patterning / Lithium-ion cells cutting Si wafer dicing/scribing / PCB micro hole drilling Scribing(thin metal ,ceramic) / Edge isolation(Solar cell) Selective removal(multi-layered film) Compound ferrite cutting / CFRP(carbon fiber reinforced plastic)cutting / Etc.(polymer, sapphire, glass, quartz..) / Bio Sensor
Dimension (W x D x H). Weight	1500 x 1200 x 1800(mm) , 4t Depending on the machining sample size.

※ Alternative laser module for different wavelength , output power can be adapted depending on the applications



Patterning system with dual mode (Direct writing and Scan mode)

## μ-Fab-D2

Dual beam delivery system makes it easy to select the beam shape (Gaussian, Top hap, Bessel mode) and working area (180mm × 180mm on scan mode, 500mm × 300mm on fixed optic mode) according to user's purpose.



# μ-Fab-D2


# μ-Fab-D2

## μ-Fab Dual mode system

- Laser source : 3-wavelength picosecond laser {IR(1064nm) / Green(532nm) / UV(355nm)}
- Dual mode system : Direct writing mode / scan mode
- Precisely small beam control
- Precisely Alignment tool : On / OFF axis type
- Easy to use with combined one software
- <40W(IR) / <20W(Green) / <10W(UV) average output power
- Enclosure safety system


## Dual mode system

- Exchangeable dual mode
  - : Automatically control the mode
- Scanner mode
  - : ~ 20um spot beam control using scanner
- Direct writing mode
  - : <10um spot beam control using motion stage




## Vision system

- Vision alignment system
- Camera 1
    - : Resolution : 1280 × 960 pixel (pixel = 3.7um × 3.75um)
    - : Field of view(FOV) : 8.0mm × 6.0mm)
  - Camera 2
    - : Resolution : 1280×960 pixel (pixel = 3.7um × 3.75um)
    - : Field of view(FOV) : 1.6mm × 1.2mm)
- Alignment accuracy : <±1um




## FTO Patterning on Glass using Direct Writing Mode


- FTO layer thickness : ~ 700 nm
- Substrate : glass (300mm x 300mm)
- Processing speed : 500mm/s at 300mm
- Patterning width : 10mm
- No damage on glass
- Isolation : >30MΩ / Current : ~ pA



## Flexible Solar Cell Patterning(P1, P2, P3) using Scan Mode



## Flexible Solar Cell Patterning(P1, P2, P3) using Scan Mode



## μ-Fab-D2 System


Laser / Wavelength	Pulsed (Nanosecond / Picosecond / Femtosecond)Single, Dual, Triple (1064nm / 532nm / 355nm)
Operation Mode	Direct Writing (Fixed Optic), Galvano Scanner
Travel Range	500mm <sup>2</sup> x 300mm <sup>2</sup> / 300mm <sup>2</sup> x 300mm <sup>2</sup> Linear Motion Stage, depends on the requirement size - Direct Writing, Fixed Optic 180mm <sup>2</sup> x 180mm <sup>2</sup> - Galvano Scanner
Accuracy	±0.5μm (Direct Writing), ±0.5μm (Scanner)
Repeatability	±0.5μm (Direct Writing), ±1μm (Scanner)
Vision Alignment	Off Axis Machine Vision System (1 Camera) - Direct Writing Off Axis Machine Vision System (2 Camera) - Scanner Drawing pattern detection. Quality control, Pattern offset alignment.
Option	Autofocusing (by Substrate Thickness Reflection)Bessel Beam, Top Hat (Flat-top), BeamPorous Ceramic Substrate Chuck (Vacuum Fix), Swirling Suction Lens Hood (Fume Removal)
Supported Drawing Format	DWG, DXF, JPEG
Application	FTO / ITO patterning / Lithium- ion cells cutting Si wafer dicing/scribing / PCB micro hole drilling Scribing(thin metal ,ceramic) / Edge isolation(Solar cell) Selective removal(multi-layered film) Compound ferrite cutting / CFRP(carbon fiber reinforced plastic)cutting / Etc.(polymer, sapphire, glass, quartz..) / Bio Sensor
Dimension (W x D x H). Weight	2650 x 1350 x 1850(mm), 5t / Depending on the machining sample size.

※ Alternative laser module for different wavelength , output power can be adapted depending on the applications

Laser Scriber with Wafer Rotary Unit

# μ-WTU


This system is laser scriber with Wafer rotary unit.



# μ-WTU


# μ-WTU

## μ-WTU configuration



Laser & Scanner	Rotary unit	Loading/unloading
<ul style="list-style-type: none"> <li>Laser optical Path</li> <li>Laser scanner</li> <li>Vison Align</li> </ul>	<ul style="list-style-type: none"> <li>Anti Vibration</li> <li>Correction of inclination</li> </ul>	<ul style="list-style-type: none"> <li>Auto leveling</li> <li>Vacuum suction Arm</li> </ul>


## Flexible Solar Cell Patterning(P1, P2, P3)



## μ-WTU (Wafer Rotation Transfer Machining)

Laser / Wavelength	Pulsed (Nanosecond / Picosecond / Femtosecond), Single (1064nm / 532nm / 355nm)
Operation Mode	Galvano Scanner
Travel Range	180mm x 180mm - Galvano Scanner
Accuracy	±0.5μm
Repeatability	±0.5μm
Vision Alignment	Off Axis Machine Vision System (2 Camera) - Scanner Drawing pattern detection. Quality control, Pattern offset alignment.
Option	Top Hat (Flat-top) Height Control (By Cartridge Storage Capacity)
Supported Drawing Format	DWG, DXF, JPEG
Application	Solar Cell (Perovskite, OPV, CIGS) / Glass / Si Wafer / Polymer / Thin metal / Printed Electronics
Dimension (W x D x H). Weight	1500 x 1000 x 1750(mm) , 2.5t

※ Alternative laser module for different wavelength , output power can be adapted depending on the applications



Laser Patterning Machine based on IFOV(Synchronization) System


# μ-Gan

This system is Laser patterning machine based on IFOV(synchronization)




## μ-Gan

### Laser processing example



50mm parallel line





80mm parallel line

## μ-Gan (Linear Gantry Stage System)

Laser / Wavelength	Pulsed (Nanosecond / Picosecond / Femtosecond) / Single, Dual, Triple (1064nm / 532nm / 355nm)
Operation Mode	Direct Write (Fixed Optic)
Travel Range	10mm <sup>2</sup> x 10mm <sup>2</sup> ~ 1500mm <sup>2</sup> x 1500mm <sup>2</sup> Linear Motion Stage (Depends on the requirement size)
Accuracy	±0.5μm
Repeatability	±0.5μm
Vision Alignment	Off Axis Machine Vision System (1 Camera) Drawing pattern detection. Quality control, Pattern offset alignment. This system is Laser patterning machine based on IFOV(synchronization)
Option	Bessel Beam, Top Hat (Flat-top) Beam, Porous Ceramic Substrate Chuck (Vacuum Fix)
Supported Drawing Format	DWG, DXF, JPEG
Application	Solar Cell (Perovskite, OPV, CIGS) / DISPLAY (FPD, AMLCD) Glass / Wafer / Polymer / Thin metal
Dimension (W x D x H). Weight	1700 x 1600 x 1650(mm), 4t, Depending on the machining sample size

※ Alternative laser module for different wavelength , output power can be adapted depending on the applications



Laser Patterning Machine based on IFOV(Synchronization) System

# μ-Fab-I


This system is Laser patterning machine based on IFOV(synchronization)



# μ-Fab-I

# μ-Fab-I




## IFOV System configuration



## μ-Fab-I (IFOV, Infinite Field of View)

Laser / Wavelength	Pulsed (Nanosecond / Picosecond / Femtosecond) / Single, Dual, Triple (1064nm / 532nm / 355nm)
Operation Mode	Synchronized Motion (Galvano Scanner + Linear Stage)
Travel Range	600mm <sup>2</sup> x 600mm <sup>2</sup> Linear Motion Stage (Depends on the requirement size)
Accuracy	±0.5μm
Repeatability	±0.5μm
Vision Alignment	Off Axis Machine Vision System (1 Camera) Drawing pattern detection. Quality control, Pattern offset alignment.
Option	Bessel Beam, Top Hat (Flat-top) Beam, Porous Ceramic Substrate Chuck (Vacuum Fix)
Supported Drawing Format	DWG, DXF, JPEG
Application	Solar Cell (Perovskite, OPV, CIGS) / DISPLAY (FPD, AMLCD)
Dimension (W x D x H). Weight	2000 x 1400 x 1750(mm), 4.5t, Depending on the machining sample size


※ Alternative laser module for different wavelength , output power can be adapted depending on the applications




Laser Patterning Machine based on Roll to Roll System

# μ-R2R

This system is laser patterning machine based on roll to roll.




## μ-R2R





### R2R Laser Patterning on Flexible Substrate / MOTF

- Laser source : 1064nm / 532nm / 355nm
- Roll Width : ≤300mm
- Material Thickness : 100 ~188μm
- Substrate : PET, PEN, Paper etc
- Processing speed : ≤3M/min
- Positional Accuracy : ≤±50μm
- Size : ~ 4150 X 1200 X 2000mm




### Application of R2R



### Printed Electronics


- Solar cell (Perovskite)
- OLED
- FPCB
- Touch Panel etc.



## μ-Fab R2R

Laser / Wavelength	Pulsed (Nanosecond / Picosecond / Femtosecond), Single (1064nm / 532nm / 355nm)
Operation Mode	MOTF, Continuous Synchronized Motion (Galvano Scanner + Web Moving)
Travel Range	Scan Area 300mm <sup>2</sup> x 300mm <sup>2</sup> ( Web Width 300mm ) (Depends on the requirement size)
Accuracy	±5μm
Repeatability	±5μm
Vision Alignment	Off Axis Machine Vision System (2 Camera – Line Scan)
Option	Top Hat Beam
Supported Drawing Format	DWG, DXF, JPEG
Application	Perovskite Composite / Flexible Film / Printed Electronics
Dimension (W x D x H). Weight	4150 x 1200 x 1550(mm), 3.5t, Total Module (unwinder-Laser Patterning-Rewinder)


※ Alternative laser module for different wavelength , output power can be adapted depending on the applications



Slot die coating System

# μ-Slot Die

This system is for slot die coating and drying.



## μ-Slot Die System

Travel Range	Slot Head Width 200mm ~ 300mm (Depends on the requirement size)
Option	Slot-die Head Lip Cleaner IR Thermal Drying Chamber
Application	Perovskite Composite / Flexible Film / Printed Electronics
Dimension (W x D x H). Weight	1700 x 1600 x 1650(mm), 4t, Depending on the Coating sample size

※ Alternative laser module for different wavelength , output power can be adapted depending on the applications

LASER PATTERNING SYSTEM

# μ-Lab CO<sub>2</sub>

It is able to get the excellent performance of the cutting edges with minimum burr and debris particles applying the CO<sub>2</sub> laser beam by Scan Mode




# μ-Lab CO<sub>2</sub>

# μ-Lab CO<sub>2</sub>

## Application – Leather

Laser power	Freq.	Mark speed	Pulse width	pass	Line lengths(set/real)
100%	15kHz	300mm/s	5us	4	1238mm / 1210mm




## μ-Lab CO<sub>2</sub>

Laser / Wavelength	CW (Output 300W), Single (10600nm)
Operation Mode	Galvano Scanner (Spot Diameter - 60μm)
Travel Range	Scan Area Max 1250mm <sup>2</sup> x 1250mm <sup>2</sup>
Accuracy	±5μm (@1250mm <sup>2</sup> X 1250mm <sup>2</sup> )
Repeatability	±5μm (@1250mm <sup>2</sup> X 1250mm <sup>2</sup> )
Vision Alignment	-
Option	Focus Shifter (Focus Point Height Leveling)
Supported Drawing Format	DWG, DXF, JPEG
Application	Large Area Cutting
Dimension (W x D x H). Weight	2500 x 1200 x 1750(mm) , 1.0t


※ Alternative laser module for different wavelength , output power can be adapted depending on the applications

## Polymer film cutting (Thickness : 180um, 66W, 800mm/s, pulse width : 5us)



Width\_upper side

Vertical\_upper side




Width\_bottom side

Vertical\_bottom side

# KOS Software



# KOS Software

## KOS Software Introduction




## Laser Spot Overlap – LSO(%)

Adjustment of LSO can improve processing quality.




## Auto measure power / Generate Graph

Automatically calculate and graph power and pulse energy based on the reposition rate.



## LSO 3D Chart


It is possible to generate 3D chart by functioning speed of Scanner and repetition rate of Laser.



# KOS Software

## Measure Function

Enable digitization of fine processed data by optimized vision systems.



## Auto Focus

Positioning of machining Z suitable for sample thickness.

Aligning Item	Wavelength	Item Note	Aligning Width	Aligning Height	Item Thickness
Item 2	UV	None	100	100	1
Item 3	UV	None	65	50	0.05
Item 4	UV	None	0	0	0
Item 5	UV	None	0	0	0

Auto Focus Click to select the appropriate machining Z location

# KOS Software

## Control Laser Parameter

When the user performs multiple repetitive tests to find the best process parameter, Ability to apply multiple different parameter values to processing samples at a time to increase work efficiency.

Power Level	Spot Dia.(um)	LSO(%)	Power (Watt)	Fluence(J/cm^2)	Attenuator Power Level(%)	Machining Z Offset (mm)	Pass #	Group Delay (s)	Group Note
100	20	99	10	6.36619772367581	60	-1	1	1	
300	20	99	10	6.36619772367581	100	-2	1	1	
300	20	99	10	6.36619772367581	100	0.5	1	1	
300	20	99	10	6.36619772367581	100	-1.56	1	1	
300	20	99	10	6.36619772367581	100	1.55	1	1	



## Auto Vision Align

Alignment using vision camera




# KOS Software

# Sample test service





## Application - Polymer



## AI adoption


Optimization of process parameters through learned data



# Sample test service

# Sample test service


## Application - Wafer (Ceramics)




**Drilling of Si-Wafer**  
Wavelength : 1064nm  
Pulse energy :  
Rep rate : 10kHz



**Si Wafer Round Cutting**  
Wavelength : 532nm  
Thickness : 520µm




**Edge Isolation of Si Solarcell**  
Wavelength : 1064nm  
Pulse energy :  
Rep rate : 500kHz




**Si Wafer Pattern Cutting**  
Wavelength : 532nm




**Removal of TCO on CIGS + Mo Glass**  
Wavelength : 1064nm




**Removal of CIGS on Mo+Glass**  
Wavelength : 1064nm  
Pulse energy :  
Rep rate : 500kHz



**Silicone Sheet Hole Drilling**  
Wavelength : 355nm



**AlN Wafer Hole Drilling**  
Wavelength : 355nm




**Si Wafer Pattern Cutting**  
Wavelength : 532nm



**Si Wafer Drilling**  
Wavelength : 532nm




**Si Wafer Align Key Marking**  
Wavelength : 355nm




**Ceramic Hole**  
Wavelength : 10.6µm


## Application - Metal




**Au Pad Full Scribing**  
Wavelength : 355nm



**Copper Foil Hole Drilling**  
Wavelength : 532nm




**Back Electrode Film Ablation (ZnO on the Glass)**  
Wavelength : 355nm




**Ag Nano Wire Thin-film Scribing**  
Wavelength : 1064nm




**Cu Hole Drilling**  
Wavelength: 355nm  
Thickness : 0.1mm



**SUS Hole Drilling**  
Wavelength : 355nm  
Thickness : 0.1mm




**Alumina Tube Hole Drilling**  
Wavelength : 10.6µm



**Metal Film Patterning**  
Wavelength : 355nm




**SUS304 Hole Drilling**  
Wavelength : 355nm



**Aluminium Through Line Patterning**  
Wavelength : 532nm



**Metal Oxide Film Ablation**  
Wavelength : 532nm




**Si Wafer Metal Layer Ablation**  
Wavelength : 355nm


# Sample test service

# SLM(Spatial Light Modulators)


## Application - Transparent Materials & Etc.



**Quartz Micro-Hole Drilling**  
(Cross-Section)  
Wavelength : 355nm




**Sapphire Micro-Hole Drilling**  
Wavelength : 355nm  
Thickness : 420µm




**Soda-Lime Glass Hole Scribing (Via Hole)**  
Wavelength : 355nm




**Epoxy Resin Patterning**  
Wavelength : 10.6µm




**Superconductor GdBCO Thin Film Scribing**  
(Cross-Section)  
Wavelength : 355nm




**Superconductor GdBCO Thin Film Hole Drilling (Through Hole)**  
Wavelength : 355nm



**Quartz Scribing**  
Wavelength : 10.6µm



**Flexible Gorilla Glass Cutting**  
Wavelength : 355nm




**Slide Glass Cutting**  
Wavelength : 355nm



**Graphene Cutting**  
Wavelength : 355nm




**Carbon Disk Hole Drilling (100% Carbon)**  
Wavelength : 355nm





**Quartz Hole Patterning (Via Hole)**  
Wavelength : 355nm


## Application – Glass / Medical



High precision glass drilling



Stainless steel stent cutting



**Diffractive Optics**



**Spatial Light Modulators**



**LCOS Microdisplays**



**Custom LCOS Components**

